



S707

30, 60, 90 & 120 MINUTES
FIRE PROTECTION

ON-SITE & OFF-SITE WATERBORNE
decorative intumescent coating
FOR STRUCTURAL STEEL

Nullifire[®]

TAKING THE LEAD IN BETTER FIRE PROTECTION

Nullifire S707
water-based solutions
offer faster, safer and
more economical
fire protection to
internal steelwork than
solvent-based solutions



S707

30, 60, 90 & 120 MINUTES FIRE PROTECTION

ON-SITE & OFF-SITE WATERBORNE decorative intumescent coating FOR STRUCTURAL STEEL

ENVIRONMENTALLY FRIENDLY SYSTEM

Water-based and halogen free, the S707 range has low VOC content, making it suitable in less well ventilated areas.

S707 is ready to use (requiring no thinning) and is easy to spray. Conventional airless manual or automated spray systems may be used. S707 may be applied by roller or brush, using a 'laying on' technique to avoid heavy brush marks.

SMOOTH, HARD- WEARING FINISH

S707-60 is white and S707-120 is light grey in colour. Both products dry to a smooth, robust finish. This avoids the need for top seal in non-decorative areas of C1 buildings*, providing even faster and more economical construction times.

PROTECTION AND DECORATION

The S707 range of fast drying, water-based decorative intumescent coatings are designed for on-site and off-site application. S707 can remove the need for top seal in non-decorative C1 buildings*.

S707 Range

- **Fully tested and approved**
 - BS476: Part 20/21: 1987, in line with the ICF and ASFP guidelines for 30, 60, 90 and 120 minutes
 - Surface spread of flame and propagation tested to BS476: Part 6/7, Class 0
 - Smoke and Toxicity tested to EN 13823 (SBI) and IMO smoke/toxicity
 - Fully tested on Cellular beams in accordance with the ASFP method
 - Yellow Book and ICF approved
- **Hi-Solids content**
 - For thinner film and faster drying time
- **Hi-Build technology**
 - For single coat application, providing exceptional results – faster





COMPREHENSIVE RANGE

S707-60 System

30, 60 and 90 minutes fire protection in a single coat, providing faster application

Reducing application time

- Reducing overall site costs
- Reducing possible health and safety risks to other trades and the general public

Solvent free system

- Low odour
- Low VOC content
- Low risk
- Environmentally friendly

Smooth decorative finish

- No top seal required in non-decorative C1 Buildings*
- Reduced costs
- Reduced application time

S707-120 System

Water-based coating with 90 and 120 minutes fire protection

- Up to 30% faster drying/overcoating times compared to traditional solvent-based systems
- No solvent entrapment, or prolonged solvent odour
- Smooth hard finish, unlike traditional solvent-based systems, which tend to remain soft and susceptible to damage

Solvent free system

- Low odour
- Low VOC content
- Low risk
- Environmentally friendly

Smooth decorative finish

- No top seal required in non-decorative C1 building*
- Reduced costs
- Reduced application time

		S707-60 Water-based Intumescent Basecoat	S707-120 Water-based Intumescent Basecoat
Properties	Area of Use	Internal	Internal
	S.G	1.35	1.37
	Volume Solids	72%	68%
	Flash Points	>55°C	>55°C
	Colour	White	Light Grey
Technical	Preparation	Onto clean dry compatible primer	Onto clean dry compatible primer
	WFT/Coat µm	Brush: <1000 Spray: <1600	Brush: <1000 Spray: <1500
	DFT/Coat µm	Brush: <720 Spray: <1152	Brush: <680 Spray: <1020
	Drying Times	24 hours between coats at >10°C	24 hours between coats at >10°C
	Over Coating	Minimum 24 hours at >10°C before top coat	Minimum 24 hours at >10°C. Heavy loadings may require longer top coat
	Fire Performance	30, 60 and 90 minutes	90 and 120 minutes
	Steel Section	Universal, hollow sections and cellular beams	Universal, hollow sections and cellular beams
	Certification	BS476: Part 20/21 BS476: Part 6/7 Class 0 EN13823 (SBI) and IMO smoke/toxicity Certifire fully tested on cellular beams	BS476: Part 20/21 BS476: Part 6/7 Class 0 EN13823 (SBI) and IMO smoke/toxicity Certifire fully tested on cellular beams
Top Seal Requirement	Over Coating	Top seal within 1 month	Top seal within 1 month
	Building Classification	C1, C2 and C3 buildings*	C1, C2 and C3 buildings*
General	Application Method	Airless spray, short pile roller or brush	Airless spray, short pile roller or brush
	Container Size	25kg Drum	25kg Drum

*NOTE: Average drying times based on typical DFT. For building classification outside of this range please refer to Nullfire's technical services department.



C1, C2, C3 Building Classification

Guidance to the corrosion protection of steelwork, from 'The Prevention of Corrosion on Structural Steelwork' published by Corus.

C1: Very low corrosion risk, warm dry interior application, for example offices, shops, residences, schools, hospitals, airports

C2: Low corrosion risk, steelwork exposed to moisture, for example sports halls, exhibition halls, vehicle depots

C3: Medium corrosion risk, steelwork exposed to moisture and pollution, for example food processing, dairies, breweries etc.

For further information on C1, C2 and C3 Building Classifications and applications outside this range, for example stadia, swimming pools, chemical plants and other areas where steelwork is exposed to high levels of moisture or corrosive pollutants, please consult Nullfire Technical Services Department.

EXCEPTIONAL, SUSTAINABLE APPEARANCE

Top seal for S707 (where required) is available in a range of RAL or BS4800 colours. It contains no fibres, and is therefore suitable for areas where delicate electronic instruments are manufactured or used. The satin finish is easy to maintain by simply wiping clean with a damp cloth.

***NOTE:** Although the risk of damage to the intumescent coating is minimal, a repair kit is available for making good any damaged areas on site without detracting from the S707 finish or performance.



VERSATILE SYSTEM WITH PROVEN PERFORMANCE

Nullfire has pioneered the use of intumescent coatings for the decorative fire protection of structural steelwork for a generation.

S707 is the most advanced and versatile waterborne basecoat of its type. It provides a durable and attractive white surface, similar to a paint finish. However, in a fire, the S707 film expands to many times its original film thickness. This provides an insulating foam-like coating or 'char' to protect steelwork against heat build-up and the effects of fire.

The system, applied to correctly prepared steel, typically comprises two or three layers, depending upon the application:

Primer

To protect the steel against corrosion and prepare the surface. This provides a key for the application of the basecoat.

Basecoat

The S707 intumescent coating itself, applied on-site to a measured thickness to provide the specified level of fire protection.

Top Seal

A hard decorative finish to seal in the basecoat and provide an attractive, high quality appearance.

Application

Nullfire Primer, S707 Basecoat, and Top Seal are applied by fully trained specialist approved contractors, ensuring a high quality service and finish.



COMPREHENSIVE TECHNICAL SUPPORT

Nullfire S707 is backed by full technical information, including

- Loading tables
- Technical Data Sheets
- Fire engineering support
- Materials estimating program
- Application and product training

Expert support and assistance is available for every stage of a project, from product selection and specification to installation and verification.

CONTRACTS SUPPORT

Nullfire operates a unique team of fully trained contract support engineers.

They are available to assist in project management and schedule planning to meet project time scales. They also provide on-site or off-site inspection* to ensure correct application of all Nullfire products.

For information or assistance, contact Nullfire today:

Tel: 024 7685 5000

Fax: 024 7646 9547

Email: protect@nullfire.com

***NOTE:** Applicable to areas accessible for inspection only. Those parts of the structure to which access cannot be gained, for example areas made inaccessible by subsequent construction work, are outside the scope of Nullfire inspection and verification.

Nullifire®

SPECIALIST EXPERTISE YOU CAN RELY ON

Nullifire has been at the forefront of the development of intumescent fire protection systems for over 25 years. Totally focused on fire protection, the company has worked with the world's leading architects, providing fire protection solutions for many of the major buildings of our time.

Nullifire offers high performance, fire protective solutions for:

Steelwork

Decorative, durable off-site and on-site systems for interior and exterior steelwork

Timber

Decorative system in matt or satin clear finish and a full range of RAL and BS 4800 colours

Construction joints

Fire seals for joints, gaps and profiled metal sheeting

Service penetrations

Lightweight, flexible barriers to maintain compartmentation

Call Nullifire Technical Services Department for full details

Tel: 024 7685 5000

Fax: 024 7646 9547

Email: protect@nullifire.com

S707

30, 60, 90 & 120 MINUTES FIRE PROTECTION

ON-SITE & OFF-SITE WATERBORNE
decorative intumescent coating
FOR STRUCTURAL STEEL



All information in this brochure is provided in good faith by Nullifire Limited and is believed correct at the time of printing. Nullifire Limited reserve the right to change product specifications in line with their policy of continuing product development

Nullifire, TREMCO and
Nullifire S707 are
Registered Trade Marks

Nullifire®

Part of the **TREMCO** Group of Companies

Nullifire Limited

Torrington Avenue, Coventry
CV4 9TJ, United Kingdom

Telephone +44 (0)24 7685 5000

Facsimile +44 (0)24 7646 9547

e-mail protect@nullifire.com

website www.nullifire.com

An **PPM** Company



Certificate No. FM1764
ISO 9001:2000



certifire

TAKING THE LEAD IN BETTER FIRE PROTECTION